Slips, Trips and Falls

OHS information for employers and workers

Purpose

It's amazing that we don't fall more often than we do. As our leg swings forward each time we take a step, our toe rushes past the ground at a speed of 14 to 18 km/hr and is often less than 1 cm above it. And as we land our heel, it normally slips forward along the ground for a distance of up to 2 cm without causing us to lose our balance.

To reduce the number of slips, trips and falls at your workplace, make sure you understand why they happen and use properly designed workspaces and work methods.

What Are Slips?

Slips most commonly occur when your heel strikes the ground and you transfer your body weight to the lead foot. If this foot slips out from under you, you lose your support base and fall. Although you may often manage to recover from slips, you can easily strain muscles while trying to regain your balance.

Many lower back injuries occur when a person carrying or lifting an object tries to recover from a slip or loss of balance. To prevent slips, workers should:

 Wear appropriate footwear and keep walking surfaces clean. Using high resistance surfaces as the answer to every slipping problem should be avoided they can increase the potential for trips; and Walking surfaces should be suitable for the pushing, pulling and carrying tasks performed on them. They should provide adequate foot grip but allow wheels to roll freely. Rough, deeply textured surfaces may reduce the potential for slips but increase the potential for trips.

What Are Trips?

Trips are caused when your forward-moving leg suddenly and unexpectedly stops. Your body continues its forward motion but hasn't a foot on which to land, so you fall.

Abrupt changes in the height of a walking surface present a tripping hazard, even if the change is as little as 1 cm. Making the transition from a low-slip resistance surface such as a sand-covered loading ramp to a high-slip resistance surface such as a clean, dry, asphalt pad, can also cause you to trip.

Make a point of adapting your walking style to the surface. To prevent trips, workers should:

- Keep as few objects as possible on walking and working surfaces;
- Eliminate abrupt changes in walking surface height; and
- Where possible, replace stairs with ramps between levels. Be aware that when a ramp angle increases to as much as 20 degrees, the friction or slip resistance of the surface must increase approximately threefold in order to prevent slips.

berta

alberta.ca PH015 – February 2017 ISBN 978-1-4601-3297-5 (PDF)

Slips, Trips and Falls

What Are Falls?

According to WCB-Alberta data, in 2015 20.5 percent of Alberta's workplace lost time claims were the result of falls as follows:

- 1) 13.9 percent fall on same level;
- 2) 6.0 percent fall to lower level;
- 3) 0.6 percent other falls.

The severity of falls is often underestimated; serious injuries or death can result from falls of as little as one metre.

Unsafe ladder use, particularly in construction and maintenance, causes falls, but even stairs present a hazard. People lose their balance, slip on poor slip-resistant material on the nosing of the stair, or don't bother to use handrails, perhaps because they're carrying something.

Falls associated with the operation of vehicles and equipment are often the result of a combination of a slip, loss of balance, and misjudging the height of a surface or step. To prevent such falls, maintain three-point contact and use handles when available.

Same level falls – many inside falls are caused by slippery conditions related to:

- Poor housekeeping
 - o Dirt, grease, or contaminants on floors
- Defects
 - o Inappropriate floor surface materials
 - o Surface wear
 - Uneven or damaged surfaces

Falls from stairs – many of these are caused by:

- Poor housekeeping;
- Defects or code violations;
 - o Lack of handrails
 - Handrails at wrong height
 - Improper or changing tread/riser dimensions
- Tread surface material (descending vs ascending falls); and
- Poor lighting and visibility.


The majority of these falls are preventable.

How Do You Prevent Falls from Elevated Surfaces?

Falls from elevated work surfaces are often preceded by slips and trips. Apply the same prevention methods to elevated surfaces as for slips and trips on level surfaces. Include railings, guardrails, travel restraint, or fall arrest systems where necessary.



Slips, Trips and Falls



Get Copies of OHS Act, Regulation and Code

Alberta Queen's Printer www.qp.gov.ab.ca

Occupational Health and Safety work.alberta.ca/ohs-legislation

© 2017 Government of Alberta, Labour

This material is for information only. The information provided in this material is solely for the user's information and convenience and, while thought to be accurate and functional, it is provided without warranty of any kind. The Crown, its agents, employees or contractors will not be liable to you for any damages, direct or indirect, arising out of your use of the information contained in this material.

If in doubt with respect to any information contained within this material, or for confirmation of legal requirements, please refer to the current edition of the Occupational Health and Safety Act, Regulation and Code or other applicable legislation. Further, if there is any inconsistency or conflict between any of the information contained in this material and the applicable legislative requirement, the legislative requirement shall prevail.

This material is current to February 2017. The law is constantly changing with new legislation, amendments to existing legislation, and decisions from the courts. It is important imperative that you and keep yourself informed of the current law in this area.

This material may be used, reproduced, stored or transmitted for non-commercial purposes. The source of this material must be acknowledged when publishing or issuing it to others. This material is not to be used, reproduced, stored or transmitted for commercial purposes without written permission from the Government of Alberta, Labour.

